



Certificate number: 2109713 (2)

Issued 01/10/2021

Expires 21/09/2026

## Kiwa Regulation 4 (KUKreg4) Certification

Evaluation Guideline – Kiwa UK – EG004 – Regulation 4(1)(a)

Model number(s) – see Appendix

### Crane Ltd.

Kiwa Watertec declares that legitimate confidence exists in the products specified in this certificate and supplied by the above organisation be relied upon to comply with the Kiwa Evaluation Guideline referred above.

Which verifies the requirements of:

**Regulation 4(1)a of the Water Supply (Water Fittings) Regulations 1999 England & Wales: 2009 Northern Ireland and 2014 Byelaws Scotland.**

This certificate has been issued in accordance with the Kiwa regulations for product certification.

Signed on behalf of Kiwa Watertec

David Jay, Business Unit Manager – Authorised Signatory  
Kiwa Watertec

Publication of this certificate is allowed.

Products are intended to be used in the UK only. For other countries, other (National) requirements will apply.

See <https://www.kiwa.com/gb/en/about-kiwa/water-products/> to ensure that the certificate is still valid.

CERTIFICATE

#### Kiwa Watertec

(A Trading Division of Kiwa Ltd)

26A Rassau Industrial Estate

Ebbw Vale

Gwent

NP23 5SD

United Kingdom

T +44 (0)1495 308185

[uk.water@kiwa.com](mailto:uk.water@kiwa.com)

[www.kiwa.co.uk](http://www.kiwa.co.uk)

#### Certificate Issued to:

Crane Ltd

Crane House

Epsilon Terrace

West Road

Ipswich

Suffolk

IP3 9FJ



# Product Certificate

Appendix to Certificate number: 2109713

The following products belong to this certificate

<p><b>PRODUCT DESCRIPTION</b>          Range of spherical valves with bronze body, chrome plated DZR brass ball (sizes ½" to 2") and bronze ball (sizes 1 ¼" to 2")          PTFE seat and single lever operating member.          ATS3 – Without Production Surveillance.</p>
<p><b>MODEL(S)</b>          D171 – ½", ¾", 1", 1¼", 1½", 2", 2½", 3";          D171EXS - ½", ¾", 1", 1¼", 1½", 2", 2½", 3";          D171T - ½", ¾", 1", 1¼", 1½", 2";          D171LS - ½", ¾", 1", 1¼", 1½", 2";          D171MHU - ½", ¾", 1";          D171MHULS - ½", ¾", 1";          D171.AT - ½", ¾", 1", 1¼", 1½", 2", 2½", 3";          D171EXS.AT - ½", ¾", 1", 1¼", 1½", 2", 2½", 3".</p>
<p><b>SIZE:</b>          See model.</p>
<p><b>SCOPE:</b>          Supplier recommended maximum working pressure 25 Bar &amp; maximum operating temperature 85°C.          Hygienic Purposes: Non-metallic materials suitable for continuous use up to 85°C.          Above ground use only.</p>
<p><b>MARKING</b>          Crane, PN25 and size cast to body.</p>
<p><b>MATERIALS</b>          Non-metallic materials assessed (BS6920) to point of discharge.</p>
<p><b>BACKFLOW PROTECTION NOTES</b>          N/A.</p>
<p><b>ADDITIONAL NOTES</b>          All water contact &amp; exposed components satisfy opacity requirements.</p>

**Extra Notes**