



Certificate number: 2101701

Date issued 6th January 2021

Date expired 5th January 2026 Original/Amendment *Original*

Kiwa UK Regulation 4 (KUKreg4) Approval

ATS3 – Without Production Surveillance

Issued by Kiwa Watertec (UK)

Evaluation Guideline: Kiwa UK – EG004
Reference Standards: Regulators Specification
Model Designations: see Appendix

Factor: Crane Limited.

Kiwa Watertec declares that legitimate confidence exists in the products specified in this certificate and supplied by the above organisation be relied on to comply with the above Evaluation Guideline and Standards, and can be marked with the KUKreg4mark.

The intended use of this certificate is for compliance with Regulation 4(1)a of the Water Supply (Water Fittings) Regulations 1999 England & Wales; 2009 Northern Ireland and 2014 Byelaws Scotland

This certificate has been issued in accordance with the Kiwa regulations for product certification, which is managed in accordance with ISO/IEC 17065.

Signed on behalf of Kiwa Watertec

David Jay,
Business Unit Manager – Authorised Signatory
Kiwa Watertec

CERTIFICATE

390170301

Kiwa Watertec
(A Trading Division of Kiwa Ltd)
26A Rassau Industrial Estate
Ebbw Vale
Gwent
NP23 5SD
United Kingdom
T +44 (0)1495 308185
uk.water@kiwa.com
www.kiwa.co.uk

Certificate issued to:

Crane Ltd
Crane House
Epsilon Terrace
West Road
Ipswich
Suffolk
IP3 9FJ



The following products are covered by this certificate -

PRODUCT DESCRIPTION: Range of non-verifiable double check valve assemblies consisting of two spring loaded resilient trim in-line check valve cartridges housed in a DZR brass body, compression models are nickel plated. A drain port is provided between the cartridges. Compression models are to be used with copper pipe to EN1057. Maximum working pressure 16.0 Bar. Maximum operating temperature for the D220W range 85°C. Maximum operating temperature of the D200CW range 60°C. ATS3 – Without Production Surveillance.
MODEL(S): D220W – DN15, DN20, DN25, DN32, DN40, DN50; D220CW – 15mm, 22mm, 28mm.
SIZE: See model.
SCOPE: Manufacturer recommended maximum working pressure 16.0 Bar. Maximum operating temperature for the D220W range 85°C. Maximum operating temperature of the D200CW range 60°C. Hygienic purposes: Non-metallic materials suitable for continuous use up to 85°C for the D220W & 60°C for the D200CW. Above ground use only.
MATERIALS: Non-Metallic materials assessed (BS6920) to point of discharge.
BACKFLOW PROTECTION NOTES: N/A.
MARKING: Crane, flow arrow, PN, DN and CR mould on body.
ADDITIONAL NOTES: All water contact & exposed components satisfy opacity requirements.

Extra Notes: