Reflex Refix DE 1000, diaphragm expansion vessel without through flow, blue, 10/2 bar





Features

Туре	DE 1000
Colour	blue
Diaphragm material	butyl
Nominal volume	1000 I
Max. useful volume	8001
Max. permissible system temperature	70 °C
Min. perm. operating temperature	-10 °C
max. perm. operating temperature	70 °C
max. perm. operating pressure	10 bar
Factory provided gas supply pressure	2 bar
Connection	G 11/2"
Diameter	740 mm
Height	2804 mm
High water connection	261 mm
Tilt dimension approx.	2827 mm
Weight	210.00 kg

Description

Refix DE

Non-flowed through diaphragm expansion tank for water supply installations that are not subject to DIN 1988, e.g. fire extinguishing and service water systems, underfloor heating or heat source installations. Vessels fitted according to DIN EN 13831. Approval according to Pressure Equipment Directive 2014/68/EC.

- bladder according to DIN EN 13831 / replaceable from 50 litres
- for antifreeze additive of at least 25 50 %
- parts in contact with water are corrosion-protected
- durable epoxy resin coating
- 33 litres with brackets, from 50 litres with adjustable feets
- the following types incl. pressure gauge:
 - \rightarrow 10/16 bar: from Ø 1,000 mm
 - \rightarrow 25 bar: from Ø 450 mm
- pressure gauge and supply pressure valve protected by clip

Note:

No licence requirement according to SWKI HE301-01 and SVTI for (PSV * VN \leq 3,000 bar * litre).

